


# 8A4D LTP

## SPECIFICATIONS

Nominal Voltage (V)	12V
Capacity at C/100	216Ah
Weight	129 (58.5 kg)
Plate Alloy	Lead Calcium
Posts	Forged terminals & bushings
Container/Cover	Polypropylene
Operating Temperature Range	-40°F (-40°C) – 140°F (60°C)
Charge Voltage @ 68°F (20°C)	
Cycle	2.40 - 2.43 VPC
Float	2.25 - 2.30 VPC
Vent	Self-sealing (2 PSI operation)
Resistance	3.0 Milliohms (full charge)
Terminal	T975



Rated non-spillable by ICAO, IATA and DOT  
Approved by CEC

Made in the U.S.A by East Penn Manufacturing

Distributed by:


Valve-Regulated, Absorbed Glass Mat Technology



## DIMENSIONS

Length (mm)	20.75 (527 mm)
Width (mm)	8.5 (216 mm)
Height (mm)	11 (279 mm)

## Cycling Ability



Number of cycles vs. depth of discharge  
at +20°C  
discharge with 20 hour rate

**MK Battery**

1645 South Sinclair Street • Anaheim, California 92806  
Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-Mail: sales@mkbattery.com

